Provide high efficiency filtration for the removal of sediment in water supplies, removing sand, silt, dirt and rust particles.

Ideal for:

- Mains drinking water Rainwater
- Dam water / Bore water
- Pretreatment for UV treatment systems

Available in 1 micron, 5 micron, 20 micron and 50 micron

ECO-PURE POLY PLEATED

Ideal for removal of sand, silt, dirt and rust particles from drinking water. These elements have up to 7 times more holding capacity than traditional rope wound elements Suitable for repeated re-use by simply washing in warm soapy water.

- High flow rates improving water pressure and flow
- Pre-treatment for poly spun elements and UV treatment systems High dirt holding capacity lengthens cleaning intervals

Available in 20micron

ECO-PURE BLOCK ACTIVATED CARBON

Designed to remove unpleasant taste and odours as well as removing fine sediment. This design makes it an excellent filter for removing contaminants, to ultimately produce cleaner, clearer and simply better tasting water.

Removes:

- Bad Taste and Odour
- Pesticides and agricultural sprays
- Metals such as lead

Available in 5micron

PRICE (inc. GST)

MODEL	MICRON	PRICE (inc. GST)	CODE
POLY SPUN 10"	1micron	\$3.90	5571020000
	5micron	\$3.90	5571030000
	20micron	\$3.90	5571050000
	50micron	\$3.90	5571060000
POLY PLEATED 10"	20micron	\$7.60	5571250000
BLOCK ACTIVATED CARBON 10"	5micron	\$9.40	5572120000

POLY SPUN JUMBO 10"	20micron	\$16.80	5571150000
	50micron	\$16.80	5571160000
POLY PLEATED JUMBO 10"	20micron	\$24.10	5572050000
BLOCK ACTIVATED CARBON JUMBO 10"	5micron	\$37.00	5572220000

POLY SPUN 20"	1micron	\$9.40	5574020000
	20micron	\$9.40	5574050000
	50micron	\$9.40	5574060000

POLY SPUN JUMBO 20"	20micron	\$35.20	5574150000
	50micron	\$35.20	5574160000
POLY PLEATED JUMBO 20"	20micron	\$37.00	5575050000

FLOW RATE

ТҮРЕ	FLOW RATE CAPACITY	POLY SPUN (lpm)	POLY PLEATED (lpm)	BLOCK ACTIVATED CARBON (Ipm)
10 " STANDARD	4x 🎩	40	50	20
10 " JUMBO	8x 🍒	80	100	35
20 " JUMBO	16 x 🍒	160	200	50

* 🛴 = 10 lpm at 1.5bar (22psi) with 20micron filter. Averaged lpm of the 3-6 month life span

Maximum 2 of the same product per person per purchase on all Central Districts Field Days specials stock. Specials valid until 30th April 2014 or while stocks last.







CENTRAL DISTRICTS FIELD DAYS **SPECIALS**

eg.

10" FILTER HOUSING KIT

Ideal for point of use, the 10" filter housing kit has a unique advantage of being compact and durable, making it suitable for use in a range of different situations at work or home. The clear bowl is ideal for monitoring filter condition, however must be protected from sunlight to prevent bacteria growth.

BENEFITS

durable and economical

easy to install

easy monitoring of filter cartridge condition



SUITABLE FOR

under-sink kitchen

one bathroom

small house

HOUSING KIT INCLUDES





Poly Spun 20micron filter

Max Working Pressure




8 bar (116psi)

45°C (113°F)

25mm (1")







Invercargill

Auckland

Brisbane

Palmerston North

Christchurch

Auckland

Brisbane

Palmerston North

Christchurch











10" JUMBO FILTER HOUSING KIT

Ideal for the complete house system the 10"JUMBO filter housing kit offers the versatility to meet all of your large-capacity filtration needs. The large housing allows for greater cartridge capacity, suitable for high-flow and heavy sediment applications. The housing bowls are constructed of durable reinforced polypropylene.

Mounting bracket and 4 x screws

BENEFITS

robust ribbed housing suitable for internal or external use flow rates up to 100 lpm



small house

HOUSING KIT INCLUDES





Poly Spun 20micron filter



Max Working Pressure	8 bar (116psi)
Max Working Temperature	45°C (113°F)
Inlet/Outlet Size	25mm (1")



SUITABLE FOR

two bathrooms



HOUSING KIT INCLUDES



20" JUMBO FILTER HOUSING KIT

Ideal for the complete large house system the 20" JUMBO filter housing kit offers the versatility to meet all of your extra large-capacity filtration needs. The large housing allows for greater cartridge capacity, suitable for high-flow and heavy sediment applications.

Max Wo	orking Pressure	8 bar (116psi)
Max W	orking Temperature	45°C (113°F)
Inlet/O	utlet Size	32mm (1 1/4")

SUITABLE FOR

small irrigation

three bathrooms

double story house



BENEFITS

robust ribbed housing

suitable for internal or external use

> flow rates up to 200 lpm

HOUSING KIT INCLUDES







10" TWIN FILTER HOUSING KIT

Ideal for point of use, the 10" twin filter housing kit combines the benefits of the poly spun filter cartridge producing cleaner, clearer and simply better tasting water.

CODE: 5570250000

Max Working Pressure	8 bar (116psi)
Max Working Temperature	45°C (113°F)
Inlet/Outlet Size	6.35mm (1/4")

SUITABLE FOR

under-sink kitchen



BENEFITS

clean healthy drinking water

complete system

quick and easy installation













Brisbane

Palmerston North

Christchurch